## **Copy of Pending Claims**

This listing of claims is a courtesy copy of the pending claims. No amendments have been made in this Reply.

## **Listing of Claims:**

1. (original) A method for establishing headroom for a mobile station operating in a wireless communication system comprising the steps of:

determining a communication channel variance condition; and establishing a headroom value based on the communication channel variance condition.

- 2. (original) A method according to claim 1 wherein a mobile station performs the steps of determining and establishing.
- 3. (original) A method according to claim 2 wherein the mobile station determines a maximum data rate based on the headroom value and sends the maximum data rate to a base station.
- 4. (original) A method according to claim 2 wherein the mobile station determines a maximum data rate based on the headroom value and sends a rate adjustment request to a base station.
- 5. (original) A method according to claim 2 further comprising the steps of: detecting a battery condition of the mobile station; and modifying the headroom value based on the battery condition.

6. (original) A method according to claim 5 wherein the step of modifying the headroom value based on the battery condition comprises:

determining if the battery condition relates to a low battery level; and if the battery condition relates to a low battery level, increasing the headroom value.

- 7. (original) A method according to claim 2 wherein the step of determining a communication channel variance condition includes measuring a variance in a primary pilot power.
- 8. (original) A method according to claim 1 wherein a base station performs the steps of determining and establishing.
- 9. (original) A method according to claim 8 wherein the step of determining a communication channel variance condition includes examination of an inner loop power control bit stream.
- 10. (original) A method according to claim 8 further comprising the step of: sending the headroom value to the mobile station.
- 11. (original) A method according to claim 8 further comprising the step of: determining a data rate assignment for a mobile station using the headroom value and sending the data rate assignment to the mobile station.
- 12. (original) A mobile station comprising: means for determining a communication channel variance condition; and means for establishing a headroom value based on the communication channel variance condition.

- 13. (original) A mobile station according to claim 12 further comprising: means for determining a maximum data rate based on the headroom value; and means for sending the maximum data rate to a base station.
- 14. (original) A mobile station according to claim 12 further comprising: means for determining a maximum data rate based on the headroom value; and means for sending a rate adjustment request to a base station.
- 15. (original) A mobile station according to claim 12 further comprising: means for detecting a battery condition of the mobile station; and means for modifying the headroom value based on the battery condition.
- 16. (original) A wireless communication system comprising:
  a base station;
  at least one mobile station;
  means for determining a communication channel variance condition; and
  means for establishing a headroom value based on the communication channel variance
  condition.
- 17. (original) A wireless communication system according to claim 16 further comprising: means for determining a data rate based on the headroom value.
- 18. (original) A wireless communication system according to claim 17 further comprising: means for sending the data rate between the base station and said at least one mobile station.
- 19. (original) A wireless communication system according to claim 16 further comprising: means for determining a battery condition of said at least one mobile station; and means for modifying the headroom value based on the battery condition.

20. (original) A wireless communication system according to claim 19 further comprising: means for determining a data rate based on the headroom value; and means for sending the data rate between said at least one mobile station and the base station.